

## B-Sight



This top-notch surveillance series promises exceptional value for money, with superior image quality and enhanced night performance. Their durable aluminum alloy and polycarbonate construction ensure longevity and reliability, making them perfect for your security needs.



# BSH-340IPBN-28

## 4MP Fixed Lens Bullet Camera with Hybrid LED and DDA1 Analytics

This 4MP hybrid bullet camera is made of aluminum alloy and polycarbonate. With its hybrid capability, the white LED will enlighten the scene when humans being detected. It's designed for short-distance surveillance (up to 20m) in indoor and outdoor scenarios. With its excellent performance, reliability, and affordable price, the BSH-340IPBN-28 camera is the perfect solution for basic installations.



## MAIN FEATURES

- BSH-340IPBN-28 4MP Fixed Lens Bullet Camera with Hybrid LED and DDA1 Analytics
- Sensor: 1/3" CMOS (16:9)
- Resolution: 2560×1440 25/30FPS (4MP)
- Lens: 2.8mm (93°)
- True Day&Night – ICR
- Illumination: 20m (1 High-Power IR LED) + 20m (1 High-Power White LED)
- Compression: H.265+ / H.264+ / H.265 / H.264 / MJPEG
- Human & Vehicle Recognition: Sterile Area, Line Crossing Human only
- Digital WDR, BLC, HLC, ROI
- Built-in Microphone
- ONVIF: Profile S
- Water Proof: IP67
- Weight: ~300g
- Power: DC12V/~350mA / PoE/~4.5W



<https://provision-isr.com>

## SPECIFICATIONS

3rd Party Cyber Protection	
General	N/A
Protection Methods	N/A
NDAA Compliant	
NDAA Compliant	Yes
Video	
Image Sensor	1/3" CMOS (16:9)
Effective Pixels	2560x1440
Electronic Shutter	1/3s ~ 1/100000s
Day & Night	ICR
Min. Illumination	Day: 0.1lux / Night: 0.9lux (@F2.2, AGC on) 0lux with IR/LED on
Audio	
Audio compression	G.711A/G.711U
Communication	One-Way Audio
Image	
Image Settings	AWB, AGC Adjustable, Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
Image Enhancement	Digital WDR, BLC, HLC, ROI
Noise Reduction	3D-DNR
Image Orientation	Mirror/Flip
Privacy Zone	Yes
Events and Analytics	
Analytics	Human & Vehicle Recognition: Sterile Area, Line Crossing *Human only
Motion Detection	Yes
Compression	

<b>Resolution</b>	4MP (2560x1440) / 3MP (2304x1296) / 2MP (1920x1080) / D1 / QVGA / CIF
<b>Frame Rate</b>	1-25/30FPS
<b>Video Compression</b>	H.265+/ H.264+ / H.265 / H.264 / MJPEG**
<b>Multi-Stream</b>	Master Stream: 4MP(2592x1520) / 2K (2560x1440) / 3MP / 2MP / 1MP Substream: 1MP/QVGA/D1/CIF Third Stream: QVGA/D1/CIF (1~30fps)
<b>Bit Rate</b>	64Kbps ~ 2Mbps@H.265 / 64Kbps ~ 3Mbps@H.264
<b>Encode Mode</b>	VBR/CBR
<b>Image Quality</b>	Five levels under VBR; Free adjustment under CBR

Lens	
<b>Lens (Field of View)</b>	2.8mm (93°)
<b>Iris</b>	Fixed Iris
<b>Lens Mount</b>	M12 Mount
<b>Detect</b>	57m(187ft)
<b>Recognize</b>	11m(36ft)
<b>Identify</b>	6m(20ft)

Network	
<b>User Access</b>	Supports simultaneous monitoring of up to 3 users with multi-stream real-time transmission
<b>Network Protocol</b>	IPv4, IPv6, TCP, UDP, DHCP, NTP, 802.1X, RTSP, Auto Report
<b>Remote Monitoring</b>	IE Browsing (Plug-In required), Chrome/Edge/Safari/Firefox plug-in free browsing, Ossia VMS Software, Provision Cam2 Mobile App *P2P WEB connection always requires Plugin
<b>Ethernet</b>	100Mbps
<b>ONVIF</b>	Profile S

Connectivity	
<b>Network</b>	RJ45 (+PoE)
<b>Audio Connectivity</b>	Built-in Microphone

<b>Alarm</b>	No
<b>SD Card</b>	No
<b>Wiegand</b>	N/A
<b>Power</b>	DC Socket
<b>Analog Video Output</b>	No

<b>Housing</b>	
<b>PoE</b>	Yes
<b>Illumination</b>	20m (1 High-Power IR LED) 20m (1 High-Power White LED)
<b>Power Supply</b>	DC12V/~350mA / PoE/~4.5W
<b>Protection Rate</b>	Water Proof: IP67
<b>Work Environment</b>	-30°C~60°C, 10%~90% Humidity
<b>Bracket</b>	3-Axis Bracket
<b>Dimensions</b>	172.2x73.4x74.5mm
<b>Weight (gross)</b>	~300g
<b>Hard Reset Button</b>	No

## ACCESSORIES

