

KIT AHD 4 CAMARAS 1080P, LÍNEA BASIC.



PAK4LIGHTCC2MP-28



Hybrid Modes	HD Analog + IP	4 + 1	3 + 2	2 + 3	1 + 4	0 + 5
--------------	----------------	-------	-------	-------	-------	-------

MODEL	I1-320AB-28
Image Sensor	1/3" CMOS
Image Format	16:9
Effective Pixels	1928(H)×1088(V)
Scanning System	Internal
Resolution	Digital:1920×1080, Analog:960H
Min. Illumination	0.1Lux / (0Lux IR On)
Day & Night	True Day&Night (ICR)
IR LED	12 LED (15m)
OSD Menu	Available via CoC only
CoC Support	Yes
Day & Night Mode	External / Day / Night
Backlight Compensation	Yes
S/N Ratio	≥48dB (AGC Off)
White Balance	Auto / Manual
Noise Reduce	2D-DNR
Video Output	AHD / CVI / TVI / CVBS + PAL/NTSC (Selectable by DIP switch)
Defog	No
Privacy Mask	No
Motion Detection	No
D-Effect	No
Lens (Field of View)	2.8mm (90°)
Power	DC12V±10%, ~210mA
Operation Temp.	-20°C~+45°C
Waterproof	IP66
Dimension	162.5*70*72mm
Net weight	156g

Main Features:

- 4 – Cámara 1080P Mod. I1-320AB-28
- 1 – Grabador 4 Canales 1080P Mod. SH-4100A5N-2L(MM)
- 4 – Rollos de cable Preensablado
- 1 – Adaptador DC 4 Salidas
- 1 – Fuente de Energía 12V 3A



SH-4100A5N-2L

1080P Lite

1080P



MODEL		SH-4100A5N-2L [Ossia v1.2]		
System	Compression Format		High profile H.264	
	ONVIF		Yes (For IP Channels)	
	Format		"All in 1" Hybrid (AHD / CVI / TVI / CVBS + IP)	
Video	Input	Min.	0CH Standard BNC + 5CH IP (Over Network)	
		Max.	4CH Standard BNC + 1CH IP (Over Network) - <u>Default Setting</u>	
Standard Output		HDMI(1920x1080), VGA (1280x1024, 1024x768), CVBS(Spot)		
Audio	Input		1CH RCA (2.0 Vp-p, 1 kΩ)1CH (+IP Cameras)	
	Output		1CH RCA (2.0 Vp-p, 1 kΩ)	
	Two Way Audio		Yes	
HD Analog Recording	General	Channels & Resolution	Min. No Channels (IP Channels Only)	
			Max. 4CH 1080P Lite Real-Time (With 1CH IP) - <u>Default Setting</u>	
	Recording Modes		Schedule, Manual, Motion, Sensor	
	AHD / TVI / CVI	5MP	No	
		4MP	No	
		2MP (1080P)	No	
	CVBS	2MPL (1080P Lite) and lower	30/25FPS Per Channel	
960H		30/25FPS Per Channel		
IP Recording	General	Channels & Resolution	Min. 1CH 1080P Real-Time (With 4CH Analog) - <u>Default Setting</u>	
			Max. 5CH 1080P Real-Time (No Analog CH)	
	Recording Modes		Schedule, Manual, Motion, Sensor, Analytics	
	IP	3MP And Higher	No	
		2MP and Lower	30/25FPS Per Channel	
Playback		Local / Remote	4CH/5CH	
		Search Mode	Time-Slice, Time, Event, File Management	
Backup		USB	2 USB 2.0 Port	
		Backup Format	AVI/DAT	
Remote Application	HD Analog Stream		Master Stream 1-25/30FPS@720P/1080P Lite; Sub-Stream: Up to 1-25FPS@D1	
	Analog Stream		Master Stream 1-25/30FPS@960H; Sub-Stream Up to 1-25FPS@960H	
	IP Stream		Master Stream 1-25/30FPS@1080P; Sub-Stream Up to 1-25/30FPS@D1	
	Master Stream		Up to 6Ch@Recording Resolution	
	Browser		Safari (Mac OS) IE (Windows Vista/7/8/10)	
	CMS		Yes	
	Mobile Application		Provision Cam2 for iOS/Android	
	User Access		5 Users Online with Professional Authority Management	
Alarm	Input		None Integral - IP Cameras Only	
	Output		None Integral - IP Cameras Only	
Storage	HDD		1 SATA (8TB)	
	E-SATA		No	
PTZ	Connection		RS-485 / CoC / IP-Over Network	
	Supported Protocols		Pelco D, Pelco P, Samsung, Visca, ONVIF, CoC	
	Supported Controls		Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus	
Network	Ethernet		100 Mbps (RJ-45)	
	Protocol		TCP/IP, DHCP, DDNS, NTP, SMTP, RTSP, HTTPS, FTP, SNMP, P2P	
	Bandwidth	Incoming	20Mbps (For 5 IP Channels) / 4Mbps (For 1 IP Channels)	
		Outgoing	12Mbps	
Others	Dimention		W300xD250xH50mm	
	Power Supply		12V/2A	
	Operation Temperature		0°C ~50°C	